

Pipe size NB x W.T (mm) ①	Jacket O.D x W.T (mm) ②	Insulation thickness (mm) ③	Weight in kg per	
			Meter	Std. Length (6m)
15 x 2.77	75 x 0.5	26.4	2.5	15
	101.6 x 0.5	39.7	3.0	18
	127 x 0.5	52.4	3.5	21
20 x 2.87	75 x 0.5	23.7	2.8	17
	101.6 x 0.5	37.0	3.3	20
	127 x 0.5	49.7	3.8	23
25 x 3.38	75 x 0.5	20.3	3.7	22
	101.6 x 0.5	33.6	4.2	25
	152.4 x 0.5	59.0	5.2	31
32 x 3.56	101.6 x 0.5	29.2	5.0	30
	127 x 0.5	41.9	5.5	33
	152.4 x 0.5	54.6	6.2	37
40 x 3.68	101.6 x 0.5	26.2	5.7	34
	127 x 0.5	38.9	6.2	37
	152.4 x 0.5	51.6	6.7	40
50 x 3.91	101.6 x 0.5	20.2	7.0	42
	127 x 0.5	32.9	7.5	45
	160 x 0.5	49.4	8.3	50
65 x 5.16	127 x 0.5	26.5	10.7	64
	152.4 x 0.5	39.2	11.2	67
	175 x 0.5	50.5	11.7	70
80 x 5.49	127 x 0.5	18.6	13.3	80
	152.4 x 0.5	31.3	13.8	83
	203.2 x 0.5	56.7	15.0	90
100 x 6.02	160 x 0.5	22.4	18.7	112
	175 x 0.5	29.9	19.0	114
	216 x 0.5	50.4	20.0	120
125 x 6.55	225 x 0.6	41.2	27.0	162
	254 x 0.6	55.7	27.8	167
	304.8 x 0.6	81.1	29.7	178
150 x 7.11	254 x 0.6	42.2	34.2	205
	275 x 0.6	52.7	34.8	209
	318 x 0.6	74.2	36.5	219
200 x 8.18	304.8 x 0.6	42.2	49.7	298
	318 x 0.6	48.8	50.2	301
	406.4 x 0.6	93.0	53.7	322
250 x 9.30	355.6 x 0.6	40.7	68.4	410
	406.4 x 0.6	66.1	70.8	425
	431.8 x 0.6	78.8	72.1	433
300 x 9.52	406.4 x 0.6	40.7	82.9	497
	431.8 x 0.6	53.4	84.2	505
	508.0 x 0.6	91.5	88.3	530

- ① Wall thickness is based on ASTM A53 GR.B standard weight. JIS, DIN or BS standard can be supplied upon request.
- ② Jacket wall thickness is based on galvanized lock seamed spiral tube. Heavier wall is available upon request.
- ③ Insulation thickness shown on above table indicates calculated thickness only. Actual thickness varies due to carrier pipe O.D tolerance and manufacturing dimensional tolerance.

Note : Kindly contact Ricwil or their respective agent for information if pipe diameter larger than 300 mm.